



e-MTB ENDURO

CRAFTY XR

Gloss Flame Red / Deep Purple

FRAME	Crafty 6061 Alloy Stealth Evo, e-Bike Optimized Zero Suspension System, 150mm travel, Forward Geometry, internal non-removable battery with integrated alloy cover, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 17mm axles, integrated dropout speed sensor, exclusive plastic motor covers
SIZES	S: 380mm / M: 420mm / L: 450mm / XL: 490mm
REAR SHOCK	Öhlins TTX Air 205X65mm. Settings: high speed compression lever with climb mode, low-speed compression, rebound, air preload. Trunnion top mount, 25x10mm bottom bushings
SHOCK SETTINGS	C40 compression, R60 rebound
FORK	Öhlins RXF 38 29, 170mm, TTX18 Twin Tube cartridge, tapered steerer tube, Boost 15x110mm axle, offset 44mm. Settings: high speed compression lever with climb mode, low-speed compression, rebound, air preload, ramp chamber
HEADSET	Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°
STEM	Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm barbare
HANDLEBAR	Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbare
GRIPS	Onoff Diamond, 1lock-on, 135mm
SEATPOST	Onoff Pija dropper internal, diameter 31.6mm, S size: 387x125mm, M size: 425x150mm, L/XL size: 465x170mm
SADDLE	Fizik Terra Aidon X5 145mm
FRONT BRAKE	Sram Code R, oversized 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads
REAR BRAKE	Sram Code R, oversized 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads
BRAKE LEVER	Sram Code R, tool-free reach adjust
RIMS	Mavic E-Deemax S 29, 30mm internal width, Maxtal welded, PFR, tubeless, 28 spokes
SPOKES	Mavic straightpull duple butted, contactless lacing
FRONT HUB	Mavic, Boost 15x110mm, IS 6 bolts
REAR HUB	Mavic, Boost 12x148mm, ID360 Ratched system, IS 6 bolts, XD freehub

FRONT TIRE	Maxxis Minion DHF 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead
REAR TIRE	Maxxis Minion DHR II 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead
CRANKSET	Race Face Aeffect ebike, 165mm
RINGS	Sram X-Sync 2 Eagle 34T, steel, narrow-wide, 104 BCD
PEDALS	---
CHAIN	Sram NX Eagle, 12s, Powerlock
FRONT DERRAILLEUR	---
REAR DERRAILLEUR	Sram GX Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1
SHIFT LEVERS	Sram Trigger GX Eagle, 12s, X-Actuation 1:1, single click
CASSETTE	Sram XG-1275, 10-52T, 12s
MOTOR	Bosch Performance Line CX Cruise (25Km/h) GEN4 BS3
BATTERY	Bosch Powertube 750Wh
DISPLAY	Bosch Kiox 300
DERRAILLEUR HANGER	Mondraker M068
OTHERS	---
WEIGHT	---



e-MTB ENDURO

CRAFTY RR

Gloss Marlin Blue / Racing Silver

FRAME	Crafty 6061 Alloy Stealth Evo, e-Bike Optimized Zero Suspension System, 150mm travel, Forward Geometry, internal non-removable battery with integrated alloy cover, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 17mm axles, integrated dropout speed sensor, exclusive plastic motor covers
SIZES	S: 380mm / M: 420mm / L: 450mm / XL: 490mm
REAR SHOCK	Fox Float-X LV Factory Kashima, 205x65mm. Settings: compression 3 positions lever, low-speed compression, low-speed rebound, air preload. Trunnion top mount, 25x10mm bottom bushings
SHOCK SETTINGS	CEC001 compression, Medium rebound, 0.2 volume spacer
FORK	Fox 38 29 Float GRIP2 Factory Kashima, 160mm, e-bike tuned, tapered steerer tube, Boost 15x110mm axle, offset 44mm. Settings: 3 positions with micro adjust compression, low-speed rebound, air preload
HEADSET	Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°
STEM	Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm barbare
HANDLEBAR	Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbare
GRIPS	Onoff Diamond, 1lock-on, 135mm
SEATPOST	Fox Transfer Factory Kashima internal, diameter 31.6mm, S size: 363.5x125mm, M/L size: 418.3x150mm, XL size: 475.1x175mm
SADDLE	Fizik Terra Aidon X5 145mm
FRONT BRAKE	Sram Code R, oversized 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads
REAR BRAKE	Sram Code R, oversized 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads
BRAKE LEVER	Sram Code R, tool-free reach adjust
RIMS	Mavic E-Deemax 29, 30mm internal width, welded, PFP, tubeless ready, 28 spokes
SPOKES	Mavic J-bend duple butted, contactless lacing
FRONT HUB	Mavic, Boost 15x110mm, IS 6 bolts
REAR HUB	Mavic, Boost 12x148mm, ID360 Ratched system, IS 6 bolts

FRONT TIRE	Maxxis Minion DHF 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead
REAR TIRE	Maxxis Minion DHR II 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead
CRANKSET	Race Face Aeffect ebike, 165mm
RINGS	Sram X-Sync 2 Eagle 34T, steel, narrow-wide, 104 BCD
PEDALS	---
CHAIN	Sram NX Eagle, 12s, Powerlock
FRONT DERRAILLEUR	---
REAR DERRAILLEUR	Sram GX Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1
SHIFT LEVERS	Sram Trigger GX Eagle, 12s, X-Actuation 1:1, single click
CASSETTE	Sram XG-1230, 11-50T, 12s
MOTOR	Bosch Performance Line CX Cruise (25Km/h) GEN4 BS3
BATTERY	Bosch Powertube 750Wh
DISPLAY	Bosch Kiox 300
DERAILLEUR HANGER	Mondraker M068
OTHERS	---
WEIGHT	---

**e-MTB ENDURO****CRAFTY R****Color 1:** Gloss Black / Graphite - **Color 2:** Gloss Black / Cherry Red

FRAME	Crafty 6061 Alloy Stealth Evo, e-Bike Optimized Zero Suspension System, 150mm travel, Forward Geometry, internal non-removable battery with integrated alloy cover, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 17mm axles, integrated dropout speed sensor, exclusive plastic motor covers
SIZES	S: 380mm / M: 420mm / L: 450mm / XL: 490mm
REAR SHOCK	Fox Float-X LV Performance, 205x65mm. Settings: compression 2 positions lever, low-speed rebound, air preload. Trunnion top mount, 25x10mm bottom bushings
SHOCK SETTINGS	Medium compression, medium rebound, air volume spacer 0.2
FORK	Fox 38 29 Float FIT GRIP EVOL Performance, 160mm, e-bike tuned, tapered steerer tube, Boost 15x110mm axle, 44mm offset. Settings: 3 positions with micro adjust compression, low-speed rebound, air preload
HEADSET	Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°
STEM	Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm barbare
HANDLEBAR	Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbare
GRIPS	Onoff Diamond, 1lock-on, 135mm
SEATPOST	Onoff Pija dropper internal, diameter 31.6mm, S size: 387x125mm, M size: 425x150mm, L/XL size: 465x170mm
SADDLE	Fizik Terra Aidon X5 145mm
FRONT BRAKE	Sram G2 R, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads
REAR BRAKE	Sram G2 R, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads
BRAKE LEVER	Sram G2 R, tool-free reach adjust
RIMS	Mavic E-Deemax 29, 30mm internal width, welded, PFR, tubeless ready, 28 spokes
SPOKES	Mavic J-bend duple butted, contactless lacing
FRONT HUB	Mavic, Boost 15x110mm, IS 6 bolts
REAR HUB	Mavic, Boost 12x148mm, ID360 Ratched system, IS 6 bolts

FRONT TIRE	Maxxis Minion DHF 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead
REAR TIRE	Maxxis Minion DHR II 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead
CRANKSET	Race Face Aeffect ebike, 165mm
RINGS	Sram X-Sync 2 Eagle 34T, steel, narrow-wide, 104 BCD
PEDALS	---
CHAIN	Sram SX Eagle, 12s, Powerlock
FRONT DERRAILLEUR	---
REAR DERRAILLEUR	Sram GX Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1
SHIFT LEVERS	Sram Trigger NX Eagle, 12s, X-Actuation 1:1, single click
CASSETTE	Sram PG-1210, 11-50T, 12s
MOTOR	Bosch Performance Line CX Cruise (25Km/h) GEN4 BS3
BATTERY	Bosch Powertube 750Wh
DISPLAY	Bosch Kiox 300
DERRAILLEUR HANGER	Mondraker M068
OTHERS	---
WEIGHT	---