



e-MTB ENDURO

CRAFTY CARBON RR SL

Matte Carbon UD / Gloss Marlin Blue

FRAME	Crafty Stealth Air full Carbon, e-Bike Optimized Zero Suspension System, 150mm travel, Forward Geometry, internal non-removable battery, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 17mm axles, integrated dropout speed sensor, exclusive plastic motor covers
SIZES	S: 380mm / M: 420mm / L: 450mm / XL: 490mm
REAR SHOCK	Fox Float DPS Factory Kashima evol LV, 205x65mm. Settings: Compression 3 positions lever, low-speed compression, low-speed rebound, air preload. Trunnion top mount, 25x10mm bottom bushings
SHOCK SETTINGS	Medium compression, Medium rebound, 0.4 volume spacer
FORK	Fox 36 29 Float GRIP2 Factory Kashima, 160mm, e-bike optimized, tapered steerer tube, Boost 15x110mm axle, 44mm offset, 68mm OD crown. Settings: high and low-speed compression, high and low-speed rebound, air preload
HEADSET	Acros custom for 1-1/2" head tube, angular contact bearings 40x52x7, Internal cable routing
STEM	Onoff Krypton FG 30mm, CNC, 31.8mm barbore
HANDLEBAR	Onoff Krypton Carbon 1.0, rise: 25mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbore
GRIPS	Onoff Diamond, 1lock-on, 135mm
SEATPOST	RockShox Reverb Stealth AXS, diameter 31.6mm, S size: 390x125mm, M size: 440x150mm, L/XL size: 440x170mm
SADDLE	Fizik Antares Large R1
FRONT BRAKE	Sram G2 Ultimate, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads
REAR BRAKE	Sram G2 RUltimate, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads
BRAKE LEVER	Sram G2 Ultimate, Carbon lever, SwingLink and lever pivot bearings, tools-free reach and contact point adjust
RIMS	DT Swiss HXC1501 Carbon Spline 29, 30mm internal width, hookless, tubeless ready, 28 spokes
SPOKES	DT Hybrid SP, straightpull
FRONT HUB	DT 240, Boost 15x110mm, CenterLock
REAR HUB	DT 240, Boost 12x148mm, 24T Ratchet system, CenterLock, XD freehub

FRONT TIRE	Maxxis Rekon 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead
REAR TIRE	Maxxis Rekon 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead
CRANKSET	E.13 TRS Race carbon ebike, 165mm
RINGS	Sram X-Sync 2 Eagle 34T, alloy, narrow-wide, 104 BCD
PEDALS	---
CHAIN	Sram GX Eagle, 12s, Powerlock
FRONT DERRAILLEUR	---
REAR DERRAILLEUR	Sram XX1 Eagle AXS, Type 2.1 roller bearing clutch, cage lock, long carbon cage, 1x12s, X-actuation 1:1
SHIFT LEVERS	Sram Eagle AXS, 12s
CASSETTE	Sram XG-1295, 10-50T, 12s
MOTOR	Bosch Performance Line CX Cruise (25Km/h) GEN4 BS3
BATTERY	Bosch Powertube 750Wh
DISPLAY	Bosch Kiox 300
DERRAILLEUR HANGER	Mondraker M068
OTHERS	---
WEIGHT	---



e-MTB ENDURO

CRAFTY CARBON XR

Gloss British Racing Green / Matte Carbon UD / Yellow

FRAME	Crafty Stealth Air full Carbon, e-Bike Optimized Zero Suspension System, 150mm travel, Forward Geometry, internal non-removable battery, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 17mm axles, integrated dropout speed sensor, exclusive plastic motor covers
SIZES	S: 380mm / M: 420mm / L: 450mm / XL: 490mm
REAR SHOCK	Öhlins TTX Air 205X65mm. Settings: high speed compression lever with climb mode, low-speed compression, rebound, air preload. Trunnion top mount, 25x10mm bottom bushings
SHOCK SETTINGS	C40 compression, R60 rebound
FORK	Öhlins RXF 38 M.2 29, 170mm, TTX18 Twin Tube cartridge, tapered steerer tube, Boost 15x110mm axle, offset 44mm. Settings: high speed compression lever with climb mode, low-speed compression, rebound, air preload, ramp chamber
HEADSET	Acros custom for 1-1/2" head tube, angular contact bearings 40x52x7, Internal cable routing
STEM	Onoff Krypton FG 30mm, CNC, 31.8mm barbore
HANDLEBAR	Onoff Krypton Carbon 1.0, rise: 25mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbore
GRIPS	Onoff Diamond, 1lock-on, 135mm
SEATPOST	Onoff Pija dropper internal, diameter 31.6mm, S size: 387x125mm, M size: 425x150mm, L/XL size: 465x170mm
SADDLE	Fizik Terra Aidon X5 145mm
FRONT BRAKE	Sram Code RSC, oversized 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads
REAR BRAKE	Sram Code RSC, oversized 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads
BRAKE LEVER	Sram Code RSC, SwingLink and lever pivot bearings, tools-free reach and contact point adjust
RIMS	Mavic E-Deemax S 29, 30mm internal width, Maxtal welded, PFR, tubeless, 28 spokes
SPOKES	Mavic straightpull double butted, contactless lacing
FRONT HUB	Mavic, Boost 15x110mm, IS 6 bolts
REAR HUB	Mavic, Boost 12x148mm, ID360 Ratched system, IS 6 bolts, XD freehub

FRONT TIRE	Maxxis Minion DHF 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead
REAR TIRE	Maxxis Minion DHR II 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead
CRANKSET	E.13 TRS Race carbon ebike, 165mm
RINGS	Sram X-Sync 2 Eagle 34T, steel, narrow-wide, 104 BCD
PEDALS	---
CHAIN	Sram NX Eagle, 12s, Powerlock
FRONT DERRAILLEUR	---
REAR DERRAILLEUR	Sram X01 Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1
SHIFT LEVERS	Sram Trigger GX Eagle, 12s, X-Actuation 1:1, single click
CASSETTE	Sram XG-1275, 10-52T, 12s
MOTOR	Bosch Performance Line CX Cruise (25Km/h) GEN4 BS3
BATTERY	Bosch Powertube 750Wh
DISPLAY	Bosch Kiox 300
DERRAILLEUR HANGER	Mondraker M068
OTHERS	---
WEIGHT	---



e-MTB ENDURO

CRAFTY CARBON RR

Matte Carbon UD / Gloss Cherry Red

FRAME	Crafty Stealth Air full Carbon, e-Bike Optimized Zero Suspension System, 150mm travel, Forward Geometry, internal non-removable battery, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 17mm axles, integrated dropout speed sensor, exclusive plastic motor covers
SIZES	S: 380mm / M: 420mm / L: 450mm / XL: 490mm
REAR SHOCK	Fox Float-X LV Factory Kashima, 205x65mm. Settings: compression 2 positions lever, low-speed compression, low-speed rebound, air preload. Trunnion top mount, 25x10mm bottom bushings
SHOCK SETTINGS	Medium compression, Medium rebound, 0.4 volume spacer
FORK	Fox 38 29 Float GRIP2 Factory Kashima, 160mm, e-bike optimized, tapered steerer tube, Boost 15x110mm axle, 44mm offset, 68mm OD crown. Settings: high and low-speed compression, high and low-speed rebound, air preload
HEADSET	Acros custom for 1-1/2" head tube, angular contact bearings 40x52x7, Internal cable routing
STEM	Onoff Krypton FG 30mm, CNC, 31.8mm barbore
HANDLEBAR	Onoff Krypton Carbon 1.0, rise: 25mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbore
GRIPS	Onoff Diamond, 1lock-on, 135mm
SEATPOST	Fox Transfer Factory Kashima internal, diameter 31.6mm, S size: 363.5x125mm, M/L size: 418.3x150mm, XL size: 475.1x175mm
SADDLE	Fizik Terra Aidon X5 145mm
FRONT BRAKE	Sram G2 RSC, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads
REAR BRAKE	Sram G2 RSC, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads
BRAKE LEVER	Sram G2 RSC, SwingLink and lever pivot bearings, tools-free reach and contact point adjust
RIMS	Mavic E-Deemax S 29, 30mm internal width, Maxtal welded, PFR, tubeless, 28 spokes
SPOKES	Mavic straightpull double butted, contactless lacing
FRONT HUB	Mavic, Boost 15x110mm, IS 6 bolts
REAR HUB	Mavic, Boost 12x148mm, ID360 Ratched system, IS 6 bolts, XD freehub

FRONT TIRE	Maxxis Minion DHF 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead
REAR TIRE	Maxxis Minion DHR II 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead
CRANKSET	Race Face Aeffect ebike, 165mm
RINGS	Sram X-Sync 2 Eagle 34T, steel, narrow-wide, 104 BCD
PEDALS	---
CHAIN	Sram NX Eagle, 12s, Powerlock
FRONT DERRAILLEUR	---
REAR DERRAILLEUR	Sram X01 Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1
SHIFT LEVERS	Sram Trigger GX Eagle, 12s, X-Actuation 1:1, single click
CASSETTE	Sram XG-1275, 10-52T, 12s
MOTOR	Bosch Performance Line CX Cruise (25Km/h) GEN4 BS3
BATTERY	Bosch Powertube 750Wh
DISPLAY	Bosch Kiox 300
DERRAILLEUR HANGER	Mondraker M068
OTHERS	---
WEIGHT	---



e-MTB ENDURO

CRAFTY CARBON R

Matte Carbon UD / Gloss Racing Silver

FRAME	Crafty Stealth Air full Carbon, e-Bike Optimized Zero Suspension System, 150mm travel, Forward Geometry, internal non-removable battery, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 17mm axles, integrated dropout speed sensor, exclusive plastic motor covers.
SIZES	S: 380mm / M: 420mm / L: 450mm / XL: 490mm
REAR SHOCK	Fox Float-X LV Performance, 205x65mm. Settings: compression 2 positions lever, low-speed rebound, air preload. Trunnion top mount, 25x10mm bottom bushings
SHOCK SETTINGS	Medium compression, Medium rebound, 0.4 volume spacer
FORK	Fox 38 29 Float GRIP Performance, 160mm, e-bike optimized, tapered steerer tube, Boost 15x110mm axle, 44mm offset, 68mm OD crown. Settings: 3 positions with micro adjust compression, low-speed rebound, air preload
HEADSET	Acros custom for 1-1/2" head tube, angular contact bearings 40x52x7, Internal cable routing
STEM	Onoff Krypton FG 30mm, CNC, 31.8mm barbare
HANDLEBAR	Onoff Krypton 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbare
GRIPS	Onoff Diamond, 1lock-on, 135mm
SEATPOST	Onoff Pija dropper internal, diameter 31.6mm, S size: 387x125mm, M size: 425x150mm, L/XL size: 465x170mm
SADDLE	Fizik Terra Aidon X5 145mm
FRONT BRAKE	Sram G2 RS, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads
REAR BRAKE	Sram G2 RS, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads
BRAKE LEVER	Sram G2 RS, SwingLink and lever pivot bearings, tools-free reach and contact point adjust
RIMS	Mavic E-Deemax 29, 30mm internal width, welded, PFR tubeless ready, 28 spokes
SPOKES	Mavic J-bend duple butted, contactless lacing
FRONT HUB	Mavic, Boost 15x110mm, IS 6 bolts
REAR HUB	Mavic, Boost 12x148mm, ID360 Ratched system, IS 6 bolts

FRONT TIRE	Maxxis Minion DHF 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead
REAR TIRE	Maxxis Minion DHR II 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead
CRANKSET	Race Face Aeffect ebike, 165mm
RINGS	Sram X-Sync 2 Eagle 34T, alloy, narrow-wide, 104 BCD
PEDALS	---
CHAIN	Sram NX Eagle, 12s, Powerlock
FRONT DERRAILLEUR	---
REAR DERRAILLEUR	Sram GX Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1
SHIFT LEVERS	Sram Trigger NX Eagle, 12s, X-Actuation 1:1, single click
CASSETTE	Sram XG-1230, 11-50T, 12s
MOTOR	Bosch Performance Line CX Cruise (25Km/h) GEN4 BS3
BATTERY	Bosch Powertube 750Wh
DISPLAY	Bosch Kiox 300
DERRAILLEUR HANGER	Mondraker M068
OTHERS	---
WEIGHT	---