



## e-MTB SUPER ENDURO

## LEVEL RR

Gloss Racing Silver / Yellow

<b>FRAME</b>	Level 6061 Alloy Stealth Evo, e-Bike Optimized Zero Suspension System, 170mm travel, Forward Geometry, internal non-removable battery with integrated alloy cover, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 17mm axles, integrated dropout speed sensor, exclusive plastic motor covers
<b>SIZES</b>	S: 380mm / M: 420mm / L: 450mm / XL: 490mm
<b>REAR SHOCK</b>	Öhlins TTX22M 225x75mm. Settings: high speed compression lever with climb mode, low-speed compression, rebound, spring preload. Trunnion top mount, 25x10mm bottom bushings
<b>SHOCK SETTINGS</b>	C10 compression, R35 rebound. Spring rate: S size 251 lbs, M size 297 lbs, L size 343 lbs, XL size 411 lbs
<b>FORK</b>	Öhlins RXF 38 M.2 29, 180mm, TTX18 Twin Tube cartridge, tapered steerer tube, Boost 15x110mm axle, offset 44mm. Settings: high speed compression lever with climb mode, low-speed compression, rebound, air preload, ramp chamber
<b>HEADSET</b>	Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°
<b>STEM</b>	Onoff Krypton FG 30mm, CNC, 31.8mm barbare
<b>HANDLEBAR</b>	Onoff Krypton Carbon 1.0, rise: 25mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbare
<b>GRIPS</b>	Onoff Diamond, 1lock-on, 135mm
<b>SEATPOST</b>	Onoff Pija dropper internal, diameter 31.6mm, S size: 387x125mm, M size: 425x150mm, L/XL size: 465x170mm
<b>SADDLE</b>	Fizik Terra Aidon X5 145mm
<b>FRONT BRAKE</b>	Sram Code RSC, oversized 4-piston caliper, Centerline 220mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads
<b>REAR BRAKE</b>	Sram Code RSC, oversized 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads
<b>BRAKE LEVER</b>	Sram Code RSC, SwingLink and lever pivot bearings, tools-free reach and contact point adjust
<b>RIMS</b>	e*thirteen E*Spec Plus, IW30 Hookless, 6069 Welded Aluminum 30mm internal width, tubeless ready, 28F / 32R spokes
<b>SPOKES</b>	e*thirteen custom J-bend, triple-butted alloy, alloy nipples, nipple washers
<b>FRONT HUB</b>	e*thirteen Boost 15x110mm, triple-sealed, fully machined aluminum, IS 6 bolts
<b>REAR HUB</b>	e*thirteen Superboost 12x148mm, triple-sealed, fully machined aluminum w/6-degree engagement, IS 6 bolts

<b>FRONT TIRE</b>	Maxxis Assegai 29x2.5WT, tubeless ready, 3C MAXX GRIP compound, DH casing, 60x2TPI, folding bead
<b>REAR TIRE</b>	Maxxis Assegai 29x2.5WT, tubeless ready, 3C MAXX GRIP compound, DH casing, 60x2TPI, folding bead
<b>CRANKSET</b>	Race Face Aeffect ebike, 165mm
<b>RINGS</b>	Sram X-Sync 2 Eagle 34T, steel, narrow-wide, 104 BCD
<b>PEDALS</b>	---
<b>CHAIN</b>	Sram GX Eagle, 12s, Powerlock
<b>FRONT DERRAILLEUR</b>	---
<b>REAR DERRAILLEUR</b>	Sram X01 Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1
<b>SHIFT LEVERS</b>	Sram Trigger GX Eagle, 12s, X-Actuation 1:1, single click
<b>CASSETTE</b>	Sram XG-1275, 10-52T, 12s
<b>MOTOR</b>	Bosch Performance Line CX Cruise (25Km/h) GEN4 BS3
<b>BATTERY</b>	Bosch Powertube 750Wh
<b>DISPLAY</b>	Bosch Kiox 300
<b>DERRAILLEUR HANGER</b>	Mondraker M068
<b>OTHERS</b>	---
<b>WEIGHT</b>	---

**e-MTB SUPER ENDURO****LEVEL R**

Gloss Black / Dirty White

<b>FRAME</b>	Level 6061 Alloy Stealth Evo, e-Bike Optimized Zero Suspension System, 170mm travel, Forward Geometry, internal non-removable battery with integrated alloy cover, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 17mm axles, integrated dropout speed sensor, exclusive plastic motor covers
<b>SIZES</b>	S: 380mm / M: 420mm / L: 450mm / XL: 490mm
<b>REAR SHOCK</b>	Fox DHX2 Performance Elite, 225x75mm. Settings: low-speed compression, low-speed rebound, spring preload. Trunnion top mount, 25x10mm bottom bushings
<b>SHOCK SETTINGS</b>	Medium compression, medium rebound. Spring rate: S/M size 300 lbs, L size 350 lbs, XL size 400 lbs
<b>FORK</b>	Fox 38 29 Float FIT GRIP EVOL Performance, 180mm, e-bike tuned, tapered steerer tube, Boost 15x110mm axle, 44mm offset. Settings: 3 positions with micro adjust compression, low-speed rebound, air preload
<b>HEADSET</b>	Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°
<b>STEM</b>	Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm barbare
<b>HANDLEBAR</b>	Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbare
<b>GRIPS</b>	Onoff Diamond, 1lock-on, 135mm
<b>SEATPOST</b>	Onoff Pija dropper internal, diameter 31.6mm, S size: 387x125mm, M size: 425x150mm, L/XL size: 465x170mm
<b>SADDLE</b>	Fizik Terra Aidon X5 145mm
<b>FRONT BRAKE</b>	Sram Code R, oversized 4-piston caliper, Centerline 220mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads
<b>REAR BRAKE</b>	Sram Code R, oversized 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads
<b>BRAKE LEVER</b>	Sram Code R, tool-free reach adjust
<b>RIMS</b>	Mavic E-Deemax 29, 30mm internal width, welded, PFP, tubeless ready, 28 spokes
<b>SPOKES</b>	Mavic J-bend duple butted, contactless lacing
<b>FRONT HUB</b>	Mavic, Boost 15x110mm, IS 6 bolts
<b>REAR HUB</b>	Mavic, Boost 12x148mm, ID360 Ratched system, IS 6 bolts

<b>FRONT TIRE</b>	Maxxis Assegai 29x2.5WT, tubeless ready, 3C MAXX GRIP compound, DH casing, 60x2TPI, folding bead
<b>REAR TIRE</b>	Maxxis Assegai 29x2.5WT, tubeless ready, 3C MAXX GRIP compound, DH casing, 60x2TPI, folding bead
<b>CRANKSET</b>	Race Face Aeffect ebike, 165mm
<b>RINGS</b>	Sram X-Sync 2 Eagle 34T, steel, narrow-wide, 104 BCD
<b>PEDALS</b>	---
<b>CHAIN</b>	Sram SX Eagle, 12s, Powerlock
<b>FRONT DERRAILLEUR</b>	---
<b>REAR DERRAILLEUR</b>	Sram GX Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1
<b>SHIFT LEVERS</b>	Sram Trigger NX Eagle, 12s, X-Actuation 1:1, single click
<b>CASSETTE</b>	Sram PG-1210, 11-50T, 12s
<b>MOTOR</b>	Bosch Performance Line CX Cruise (25Km/h) GEN4 BS3
<b>BATTERY</b>	Bosch Powertube 750Wh
<b>DISPLAY</b>	Bosch Kiox 300
<b>DERRAILLEUR HANGER</b>	Mondraker M068
<b>OTHERS</b>	---
<b>WEIGHT</b>	---