

BIKE 2023 / EN

SPECS LIST





e-MTB ENDURO

CRAFTY CARBON RR SL

Gloss Racing Silver / Dirty White

FRAME	Crafty Stealth Air full Carbon, e-Bike Optimized Zero Suspension System, 150mm travel, Forward Geometry, internal non-removable battery, Boost12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 17mm axles, integrated dropout speed sensor, exclusive plastic motor covers. MIND System (EU only)
SIZES	S: 380mm / M: 420mm / L: 450mm / XL: 490mm
REAR SHOCK	Fox Float DPS Factory Kashima evol LV, 205x65mm. Settings: Compression 3 positions lever, low-speed compression, low-speed rebound, air preload. Trunnion top mount, 25x10mm bottom bushings
SHOCK SETTINGS	Medium compression, Medium rebound, 0.4 volume spacer
FORK	Fox 36 29 Float GRIP2 Factory Kashima, 160mm, e-bike optimized, tapered steerer tube, Boost 15x110mm axle, 44mm offset, 68mm OD crown. Settings: high and low-speed compression, high and low-speed rebound, air preload
HEADSET	Acros custom for 1-1/2" head tube, angular contact bearings 40x52x7, Internal cable routing
STEM	Onoff Krypton FG 30mm, CNC, 31.8mm barbare
HANDLEBAR	Onoff Krypton Carbon 1.0, rise: 25mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbare
GRIPS	Onoff Desert, 1lock-on, 135mm
SEATPOST	RockShox Reverb Stealth AXS, diameter 31.6mm, S size: 390x125mm, M size: 440x150mm, L/XL size: 440x170mm
SADDLE	FIZIK Terra Aidon X1 145mm
FRONT BRAKE	Sram Code RSC, oversized 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads
REAR BRAKE	Sram Code RSC, oversized 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads
BRAKE LEVER	Sram Code RSC, SwingLink and lever pivot bearings, tools-free reach and contact point adjust
RIMS	e*thirteen Race Carbon Enduro IW30, Hookless carbon rim, 30mm internal width, tubeless ready, 28 spokes
SPOKES	e*thirteen custom Hive triple-buttet black steel, alloy nipples, nipple washers
FRONT HUB	e*thirteen Boost 15x110mm, triple-sealed, fully machined aluminum, IS 6 bolts
REAR HUB	e*thirteen Boost 12x148mm, triple-sealed, fully machined aluminum w/6-degree engagement, IS 6 bolts, XD freehub

FRONT TIRE	Maxxis Rekon 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead
REAR TIRE	Maxxis Rekon 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead
CRANKSET	E.13 TRS Race carbon ebike, 165mm
RINGS	Sram X-Sync 2 Eagle 34T, alloy, narrow-wide, 104 BCD
PEDALS	---
CHAIN	Sram GX Eagle, 12s, Powerlock
FRONT DERRAILLEUR	---
REAR DERRAILLEUR	Sram XX1 Eagle AXS, Type 2.1 roller bearing clutch, cage lock, long carbon cage, 1x12s, X-actuation 1:1 with battery cover
SHIFT LEVERS	Sram Eagle AXS Rocker paddle, 12s
CASSETTE	Sram XG-1295, 10-52T, 12s
MOTOR	Bosch Performance Line CX Cruise (25Km/h) GEN4 Smart System
BATTERY	Bosch Powertube 750Wh
DISPLAY	Bosch Kiox 300 / Bosch Mini Remote / Bosch System Controller
DERAILLEUR HANGER	Mondraker M068
OTHERS	---
WEIGHT	---



e-MTB ENDURO

CRAFTY CARBON XR

Matte Carbon / Gloss Racing Silver / Yellow

FRAME	Crafty Stealth Air full Carbon, e-Bike Optimized Zero Suspension System, 150mm travel, Forward Geometry, internal non-removable battery, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 17mm axles, integrated dropout speed sensor, exclusive plastic motor covers.Optional MIND System (EU only)
SIZES	S: 380mm / M: 420mm / L: 450mm / XL: 490mm
REAR SHOCK	Öhlins TTX Air 205X65mm. Settings: high speed compression lever with climb mode, low-speed compression, rebound, air preload. Trunnion top mount, 25x10mm bottom bushings
SHOCK SETTINGS	C20 compression, R35 rebound. Volume reducers 12.000 (2xF+1D)
FORK	Öhlins RXF 38 M.2 29, 170mm, TTX18 Twin Tube cartridge, tapered steerer tube, Boost 15x110mm axle, offset 44mm. Settings: high speed compression lever with climb mode, low-speed compression, rebound, air preload, ramp chamber
HEADSET	Acros custom for 1-1/2" head tube, angular contact bearings 40x52x7, Internal cable routing
STEM	Onoff Krypton FG 30mm, CNC, 31.8mm barbare
HANDLEBAR	Onoff Krypton Carbon 1.0, rise: 25mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbare
GRIPS	Onoff Desert, 1lock-on, 135mm
SEATPOST	Onoff Pija dropper internal, diameter 31.6mm, S size: 405x95-125mm, M size 458x120-150mm, L size: 498x140-170mm, XL size: 498x140-170mm
SADDLE	FIZIK Terra Aidon X5 145mm
FRONT BRAKE	Sram Code RSC, oversized 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads
REAR BRAKE	Sram Code RSC, oversized 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads
BRAKE LEVER	Sram Code RSC, SwingLink and lever pivot bearings, tools-free reach and contact point adjust
RIMS	Mavic E-Deemax S 29, 30mm internal width, Maxtal welded, PFR, tubeless, 28 spokes
SPOKES	Mavic straight-pull double butted, contactless lacing
FRONT HUB	Mavic, Boost 15x110mm, IS 6 bolts
REAR HUB	Mavic, Boost 12x148mm, ID360 Ratched system, IS 6 bolts, XD freehub

FRONT TIRE	Maxxis Minion DHF 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead
REAR TIRE	Maxxis Minion DHR II 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead
CRANKSET	E.13 TRS Race carbon ebike, 165mm
RINGS	Sram X-Sync 2 Eagle 34T, steel, narrow-wide, 104 BCD
PEDALS	---
CHAIN	Sram NX Eagle, 12s, Powerlock
FRONT DERRAILLEUR	---
REAR DERRAILLEUR	Sram X01 Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1
SHIFT LEVERS	Sram Trigger GX Eagle, 12s, X-Actuation 1:1, single click
CASSETTE	Sram XG-1275, 10-52T, 12s
MOTOR	Bosch Performance Line CX Cruise (25Km/h) GEN4 Smart System
BATTERY	Bosch Powertube 750Wh
DISPLAY	Bosch Kiox 300 / Bosch Mini Remote / Bosch System Controller
DERAILLEUR HANGER	Mondraker M068
OTHERS	---
WEIGHT	---



e-MTB ENDURO

CRAFTY CARBON RR

Matte Carbon / Gloss Orange

FRAME	Crafty Stealth Air full Carbon, e-Bike Optimized Zero Suspension System, 150mm travel, Forward Geometry, internal non-removable battery, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 17mm axles, integrated dropout speed sensor, exclusive plastic motor covers. Optional MIND System (EU only)
SIZES	S: 380mm / M: 420mm / L: 450mm / XL: 490mm
REAR SHOCK	Fox Float-X LV Factory Kashima, 205x65mm. Settings: compression 2 positions lever, low-speed compression, low-speed rebound, air preload. Trunnion top mount, 25x10mm bottom bushings
SHOCK SETTINGS	Medium compression, medium rebound, air volume spacer 0.2
FORK	Fox 38 29 Float GRIP2 Factory Kashima, 160mm, e-bike optimized, tapered steerer tube, Boost 15x110mm axle, 44mm offset, 68mm OD crown. Settings: high and low-speed compression, high and low-speed rebound, air preload
HEADSET	Acros custom for 1-1/2" head tube, angular contact bearings 40x52x7, Internal cable routing
STEM	Onoff Krypton FG 30mm, CNC, 31.8mm barbare
HANDLEBAR	Onoff Krypton Carbon 1.0, rise: 25mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbare
GRIPS	Onoff Desert, 1lock-on, 135mm
SEATPOST	Fox Transfer Factory Kashima internal, diameter 31.6mm, S size: 363.5x125mm, M/L size: 418.3x150mm, XL size: 475.1x175mm
SADDLE	FIZIK Terra Aidon X5 145mm
FRONT BRAKE	Sram Code RSC, oversized 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads
REAR BRAKE	Sram Code RSC, oversized 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads
BRAKE LEVER	Sram Code RSC, SwingLink and lever pivot bearings, tools-free reach and contact point adjust
RIMS	Mavic E-Deemax S 29, 30mm internal width, Maxtal welded, PFR, tubeless, 28 spokes
SPOKES	Mavic straight-pull double butted, contactless lacing
FRONT HUB	Mavic, Boost 15x110mm, IS 6 bolts
REAR HUB	Mavic, Boost 12x148mm, ID360 Ratched system, IS 6 bolts, XD freehub

FRONT TIRE	Maxxis Minion DHF 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead
REAR TIRE	Maxxis Minion DHR II 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead
CRANKSET	Race Face Aeffect ebike, 165mm
RINGS	Sram X-Sync 2 Eagle 34T, alloy, narrow-wide, 104 BCD
PEDALS	---
CHAIN	Sram NX Eagle, 12s, Powerlock
FRONT DERRAILLEUR	---
REAR DERRAILLEUR	Sram X01 Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1
SHIFT LEVERS	Sram Trigger GX Eagle, 12s, X-Actuation 1:1, single click
CASSETTE	Sram XG-1275, 10-52T, 12s
MOTOR	Bosch Performance Line CX Cruise (25Km/h) GEN4 Smart System
BATTERY	Bosch Powertube 750Wh
DISPLAY	Bosch Kiox 300 / Bosch Mini Remote / Bosch System Controller
DERAILLEUR HANGER	Mondraker M068
OTHERS	---
WEIGHT	---



e-MTB ENDURO

CRAFTY CARBON R

Matte Carbon / Gloss Desert Grey / Orange

FRAME	Crafty Stealth Air full Carbon, e-Bike Optimized Zero Suspension System, 150mm travel, Forward Geometry, internal non-removable battery, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 17mm axles, integrated dropout speed sensor, exclusive plastic motor covers. Optional MIND System (EU only)
SIZES	S: 380mm / M: 420mm / L: 450mm / XL: 490mm
REAR SHOCK	Fox Float-X LV Performance, 205x65mm. Settings: compression 2 positions lever, low-speed rebound, air preload. Trunnion top mount, 25x10mm bottom bushings
SHOCK SETTINGS	Medium compression, medium rebound, air volume spacer 0.2
FORK	Fox 38 29 Float GRIP Performance, 160mm, e-bike optimized, tapered steerer tube, Boost 15x110mm axle, 44mm offset, 68mm OD crown. Settings: 3 positions with micro adjust compression, low-speed rebound, air preload
HEADSET	Acros custom for 1-1/2" head tube, angular contact bearings 40x52x7, Internal cable routing
STEM	Onoff Krypton FG 30mm, CNC, 31.8mm barbore
HANDLEBAR	Onoff Krypton 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbore
GRIPS	Onoff Desert, 1lock-on, 135mm
SEATPOST	Onoff Pija dropper internal, diameter 31.6mm, S size: 405x95-125mm, M size 458x120-150mm, L size: 498x140-170mm, XL size: 498x140-170mm
SADDLE	FIZIK Terra Aidon X5 145mm
FRONT BRAKE	Sram DB8, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads
REAR BRAKE	Sram DB8, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads
BRAKE LEVER	Sram DB8, SwingLink and lever pivot bearings, tools-free reach and contact point adjust
RIMS	Mavic E-Deemax 29, 30mm internal width, welded, PFP, tubeless ready, 28 spokes
SPOKES	Mavic J-bend double butted, contactless lacing
FRONT HUB	Mavic, Boost 15x110mm, IS 6 bolts
REAR HUB	Mavic, Boost 12x148mm, ID360 Ratched system, IS 6 bolts

FRONT TIRE	Maxxis Minion DHF 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead
REAR TIRE	Maxxis Minion DHR II 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead
CRANKSET	Race Face Aeffect ebike, 165mm
RINGS	Sram X-Sync 2 Eagle 34T, alloy, narrow-wide, 104 BCD
PEDALS	---
CHAIN	Sram NX Eagle, 12s, Powerlock
FRONT DERRAILLEUR	---
REAR DERRAILLEUR	Sram GX Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1
SHIFT LEVERS	Sram Trigger NX Eagle, 12s, X-Actuation 1:1, single click
CASSETTE	Sram XG-1230, 11-50T, 12s
MOTOR	Bosch Performance Line CX Cruise (25Km/h) GEN4 Smart System
BATTERY	Bosch Powertube 750Wh
DISPLAY	Bosch Kiox 300 / Bosch Mini Remote / Bosch System Controller
DERRAILLEUR HANGER	Mondraker M068
OTHERS	---
WEIGHT	---



e-MTB ENDURO

CRAFTY XR

Gloss Yellow / Racing Silver

FRAME	Crafty 6061 Alloy Stealth Evo, e-Bike Optimized Zero Suspension System, 150mm travel, Forward Geometry, internal non-removable battery, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 17mm axles, integrated dropout speed sensor, exclusive plastic motor covers.
SIZES	S: 380mm / M: 420mm / L: 450mm / XL: 490mm
REAR SHOCK	Öhlins TTX Air 205X65mm. Settings: high speed compression lever with climb mode, low-speed compression, rebound, air preload. Trunnion top mount, 25x10mm bottom bushings
SHOCK SETTINGS	C20 compression, R35 rebound. Volume reducers 12.000 (2xF+1D)
FORK	Öhlins RXF 38 M.2 29, 170mm, TTX18 Twin Tube cartridge, tapered steerer tube, Boost 15x110mm axle, offset 44mm. Settings: high speed compression lever with climb mode, low-speed compression, rebound, air preload, ramp chamber
HEADSET	Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°
STEM	Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm barbare
HANDLEBAR	Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbare
GRIPS	Onoff Desert, 1lock-on, 135mm
SEATPOST	Onoff Pija dropper internal, diameter 31.6mm, S size: 405x95-125mm, M size 458x120-150mm, L size: 498x140-170mm, XL size: 498x140-170mm
SADDLE	FIZIK Terra Aidon X5 145mm
FRONT BRAKE	Sram Code R, oversized 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads
REAR BRAKE	Sram Code R, oversized 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads
BRAKE LEVER	Sram Code R, tool-free reach adjust
RIMS	Mavic E-Deemax S 29, 30mm internal width, Maxtal welded, PFR, tubeless, 28 spokes
SPOKES	Mavic straight-pull double butted, contactless lacing
FRONT HUB	Mavic, Boost 15x110mm, IS 6 bolts
REAR HUB	Mavic, Boost 12x148mm, ID360 Ratched system, IS 6 bolts, XD freehub
FRONT TIRE	Maxxis Minion DHF 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead

REAR TIRE	Maxxis Minion DHR II 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead
CRANKSET	Race Face Aeffect ebike, 165mm
RINGS	Sram X-Sync 2 Eagle 34T, steel, narrow-wide, 104 BCD
PEDALS	---
CHAIN	Sram NX Eagle, 12s, Powerlock
FRONT DERRAILLEUR	---
REAR DERRAILLEUR	Sram GX Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1
SHIFT LEVERS	Sram Trigger GX Eagle, 12s, X-Actuation 1:1, single click
CASSETTE	Sram XG-1275, 10-52T, 12s
MOTOR	Bosch Performance Line CX Cruise (25Km/h) GEN4 Smart System
BATTERY	Bosch Powertube 750Wh
DISPLAY	Bosch Kiox 300 / Bosch Mini Remote / Bosch System Controller
DERAILLEUR HANGER	Mondraker M068
OTHERS	---
WEIGHT	---



e-MTB ENDURO

CRAFTY RR

Matte Desert Grey / Graphite / Orange

FRAME	Crafty 6061 Alloy Stealth Evo, e-Bike Optimized Zero Suspension System, 150mm travel, Forward Geometry, internal non-removable battery, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 17mm axles, integrated dropout speed sensor, exclusive plastic motor covers.
SIZES	S: 380mm / M: 420mm / L: 450mm / XL: 490mm
REAR SHOCK	Fox Float-X LV Factory Kashima, 205x65mm. Settings: compression 2 positions lever, low-speed compression, low-speed rebound, air preload. Trunnion top mount, 25x10mm bottom bushings
SHOCK SETTINGS	Medium compression, medium rebound, air volume spacer 0.2
FORK	Fox 38 29 Float GRIP2 Factory Kashima, 160mm, e-bike tuned, tapered steerer tube, Boost 15x110mm axle, offset 44mm. Settings: high and low-speed compression, high and low-speed rebound, air preload
HEADSET	Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°
STEM	Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm barbare
HANDLEBAR	Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbare
GRIPS	Onoff Desert, 1lock-on, 135mm
SEATPOST	Fox Transfer Factory Kashima internal, diameter 31.6mm, S size: 363.5x125mm, M/L size: 418.3x150mm, XL size: 475.1x175mm
SADDLE	FIZIK Terra Aidon X5 145mm
FRONT BRAKE	Sram Code R, oversized 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads
REAR BRAKE	Sram Code R, oversized 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads
BRAKE LEVER	Sram Code R, tool-free reach adjust
RIMS	Mavic E-Deemax 29, 30mm internal width, welded, PFP, tubeless ready, 28 spokes
SPOKES	Mavic J-bend double butted, contactless lacing
FRONT HUB	Mavic, Boost 15x110mm, IS 6 bolts
REAR HUB	Mavic, Boost 12x148mm, ID360 Ratched system, IS 6 bolts
FRONT TIRE	Maxxis Minion DHF 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead

REAR TIRE	Maxxis Minion DHR II 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead
CRANKSET	Race Face Aeffect ebike, 165mm
RINGS	Sram X-Sync 2 Eagle 34T, steel, narrow-wide, 104 BCD
PEDALS	---
CHAIN	Sram NX Eagle, 12s, Powerlock
FRONT DERRAILLEUR	---
REAR DERRAILLEUR	Sram GX Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1
SHIFT LEVERS	Sram Trigger GX Eagle, 12s, X-Actuation 1:1, single click
CASSETTE	Sram XG-1230, 11-50T, 12s
MOTOR	Bosch Performance Line CX Cruise (25Km/h) GEN4 Smart System
BATTERY	Bosch Powertube 750Wh
DISPLAY	Bosch Kiox 300 / Bosch Mini Remote / Bosch System Controller
DERAILLEUR HANGER	Mondraker M068
OTHERS	---
WEIGHT	---



e-MTB ENDURO

CRAFTY R

Color 1: Matte Nimbus Grey / Black - **Color 2:** Gloss Marlin Blue / Black - **Color 3:** Gloss British Racing Green / Mojito Green

FRAME	Crafty 6061 Alloy Stealth Evo, e-Bike Optimized Zero Suspension System, 150mm travel, Forward Geometry, internal non-removable battery, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 17mm axles, integrated dropout speed sensor, exclusive plastic motor covers.
SIZES	S: 380mm / M: 420mm / L: 450mm / XL: 490mm
REAR SHOCK	Fox Float-X LV Performance, 205x65mm. Settings: compression 2 positions lever, low-speed rebound, air preload. Trunnion top mount, 25x10mm bottom bushings
SHOCK SETTINGS	Medium compression, medium rebound, air volume spacer 0.2
FORK	Fox 38 29 Float FIT GRIP EVOL Performance, 160mm, e-bike tuned, tapered steerer tube, Boost 15x110mm axle, 44mm offset. Settings: 3 positions with micro adjust compression, low-speed rebound, air preload
HEADSET	Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°
STEM	Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm barbare
HANDLEBAR	Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbare
GRIPS	Onoff Desert, 1lock-on, 135mm
SEATPOST	Onoff Pija dropper internal, diameter 31.6mm, S size: 405x95-125mm, M size 458x120-150mm, L size: 498x140-170mm, XL size: 498x140-170mm
SADDLE	FIZIK Terra Aidon X5 145mm
FRONT BRAKE	Sram DB8, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads
REAR BRAKE	Sram DB8, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads
BRAKE LEVER	Sram DB8, tool-free reach adjust
RIMS	Mavic E-Deemax 29, 30mm internal width, welded, PFP, tubeless ready, 28 spokes
SPOKES	Mavic J-bend double butted, contactless lacing
FRONT HUB	Mavic, Boost 15x110mm, IS 6 bolts
REAR HUB	Mavic, Boost 12x148mm, ID360 Ratched system, IS 6 bolts
FRONT TIRE	Maxxis Minion DHF 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead

REAR TIRE	Maxxis Minion DHR II 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead
CRANKSET	Race Face Aeffect ebike, 165mm
RINGS	Sram X-Sync 2 Eagle 34T, steel, narrow-wide, 104 BCD
PEDALS	---
CHAIN	Sram SX Eagle, 12s, Powerlock
FRONT DERRAILLEUR	---
REAR DERRAILLEUR	Sram GX Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1
SHIFT LEVERS	Sram Trigger NX Eagle, 12s, X-Actuation 1:1, single click
CASSETTE	Sram PG-1210, 11-50T, 12s
MOTOR	Bosch Performance Line CX Cruise (25Km/h) GEN4 Smart System
BATTERY	Bosch Powertube 750Wh
DISPLAY	Bosch Kiox 300 / Bosch Mini Remote / Bosch System Controller
DERAILLEUR HANGER	Mondraker M068
OTHERS	---
WEIGHT	---