

CRUSHER RR

Translucent Red Carbon / Black / Racing Silver

FRAME	Crusher Stealth Air Carbon front triangle, Stealth Alloy rear triangle, e-Bike Optimized Zero Suspension System, 150mm travel, Forward Geometry, integrated internal non-removable battery, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 17mm axles, integrated dropout speed sensor, exclusive plastic motor covers
SIZES	S: 380mm / M: 420mm / L: 450mm / XL: 490mm
REAR SHOCK	Öhlins TTX Air 205x65mm. Settings: high speed compression lever with climb mode, low-speed compression, rebound, air preload. Trunnion top mount, 25x10mm bottom bushings
SHOCK SETTINGS	C20 compression, R35 rebound. Volume reducers 12.000 (2xF+1D)
FORK	Öhlins RXF 38 M.2 29, 160mm, TTX18 Twin Tube cartridge, tapered steerer tube, Boost 15x110mm axle, offset 44mm. Settings: high speed compression lever with climb mode, low-speed compression, rebound, air preload, ramp chamber
HEADSET	Acros AZF-601 R1 Block Lock 120°, ZS44/28.6 top, ZS56/40 bottom
STEM	Onoff Krypton FG 30mm, CNC, 31.8mm barbare
HANDLEBAR	Onoff Krypton Carbon 1.0, rise: 25mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbare
GRIPS	Onoff Desert, 1lock-on, 135mm
SEATPOST	Onoff Pija dropper internal, diameter 31.6mm, S size: 405x95-125mm, M size: 458x120-150mm, L size: 498x140-170mm, XL size: 558x170-200mm + SHIMANO SL-MT800-IL lever
SADDLE	FIZIK Terra Aidon X5 145mm
FRONT BRAKE	Shimano Deore XT M8120, 4-piston caliper, MT-800 Ice-Tech 203mm Center Lock
REAR BRAKE	Shimano Deore XT M8120, 4-piston caliper, MT-810 Ice-Tech 203mm Center Lock
BRAKE LEVER	Shimano Deore XT M8120
RIMS	Mavic E-Deemax S 29, 30mm internal width, Maxtal welded, PFP, tubeless, 28 spokes
SPOKES	Mavic straight-pull double butted, contactless lacing
FRONT HUB	Mavic, Boost 15x110mm, Center Lock
REAR HUB	Mavic, Boost 12x148mm, ID360 Ratchet system, Center Lock, MS freehub

FRONT TIRE	Maxxis Minion DHF 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead
REAR TIRE	Maxxis Minion DHR II 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead
CRANKSET	Shimano Steps XT FC-8150 ebike, 165mm
RINGS	Shimano EP801, 34T, 104 BCD
BOTTOM BRACKET	--
PEDALS	--
CHAIN	Shimano Deore XT M8100
FRONT DERRAILLEUR	--
REAR DERRAILLEUR	Shimano Deore XT M8150-GS Di2 12s shadow plus, direct mount
SHIFT LEVERS	Shimano XT Di2 SW-M8150
CASSETTE	Shimano Deore XT M8100, 10-51 12s
MOTOR	Shimano STEPS EP801
BATTERY	Simplo internal 720Wh G3
DISPLAY	Shimano EN600
DERRAILLEUR HANGER	Mondraker M068
OTHERS	--
WEIGHT	--

CRUSHER R

Denim Blue / Midnight Blue / Racing Silver

FRAME	Crusher Stealth Air Carbon front triangle, Stealth Alloy rear triangle, e-Bike Optimized Zero Suspension System, 150mm travel, Forward Geometry, integrated internal non-removable battery, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 17mm axles, integrated dropout speed sensor, exclusive plastic motor covers
SIZES	S: 380mm / M: 420mm / L: 450mm / XL: 490mm
REAR SHOCK	Öhlins TTX Air 205x65mm. Settings: high speed compression lever with climb mode, low-speed compression, rebound, air preload. Trunnion top mount, 25x10mm bottom bushings
SHOCK SETTINGS	C20 compression, R35 rebound. Volume reducers 12.000 (2x F+1D)
FORK	Öhlins RXF 38 M.2 29, 160mm, TTX18 Twin Tube cartridge, tapered steerer tube, Boost 15x110mm axle, offset 44mm. Settings: high speed compression lever with climb mode, low-speed compression, rebound, air preload, ramp chamber
HEADSET	Acros AZF-601 R1 Block Lock 120°, ZS44/28.6 top, ZS56/40 bottom
STEM	Onoff Krypton FG 30mm, CNC, 31.8mm barbare
HANDLEBAR	Onoff Krypton 1.0, rise: 25mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbare
GRIPS	Onoff Desert, 1lock-on, 135mm
SEATPOST	Onoff Pija dropper internal, diameter 31.6mm, IX Remote lever with bearing, S size: 405x95-125mm, M size: 458x120-150mm, L size: 498x140-170mm, XL size: 558x170-200mm
SADDLE	FIZIK Terra Aidon X5 145mm
FRONT BRAKE	Sram Code Bronze Stealth, oversized 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads
REAR BRAKE	Sram Code Bronze Stealth, oversized 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads
BRAKE LEVER	Sram Code Bronze Stealth, SwingLink and lever pivot bushings, tool-free reach adjust
RIMS	Mavic E-Deemax 29, 30mm internal width, welded, PFR, tubeless ready, 28 spokes
SPOKES	Mavic J-bend double butted, contactless lacing
FRONT HUB	Mavic, Boost 15x110mm, IS 6 bolts
REAR HUB	Mavic, Boost 12x148mm, ID360 Ratchet system, IS 6 bolts, XD freehub

FRONT TIRE	Maxxis Minion DHF 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead
REAR TIRE	Maxxis Minion DHR II 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead
CRANKSET	Shimano Steps FC-EM600 ebike, 165mm
RINGS	Sram X-Sync 2 Eagle 34T, alloy, narrow-wide, 104 BCD
BOTTOM BRACKET	--
PEDALS	--
CHAIN	Sram NX Eagle, 12s, Powerlock
FRONT DERRAILLEUR	--
REAR DERRAILLEUR	Sram X01 Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1
SHIFT LEVERS	Sram Trigger GX Eagle, 12s, X-Actuation 1:1, single click
CASSETTE	Sram XG-1275, 10-52T, 12s
MOTOR	Shimano STEPS EP801
BATTERY	Simplo internal 720Wh G3
DISPLAY	Shimano EN600
DERRAILLEUR HANGER	Mondraker M068
OTHERS	--
WEIGHT	--

CRUSHER

Nimbus Grey / Vortex Grey / Bronze

FRAME	Crusher Stealth Air Carbon front triangle, Stealth Alloy rear triangle, e-Bike Optimized Zero Suspension System, 150mm travel, Forward Geometry, integrated internal non-removable battery, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 17mm axles, integrated dropout speed sensor, exclusive plastic motor covers
SIZES	S: 380mm / M: 420mm / L: 450mm / XL: 490mm
REAR SHOCK	Fox Float-X LV Performance, 205x65mm. Settings: compression 2 positions lever, low-speed rebound, air preload. Trunnion top mount, 25x10mm bottom bushings
SHOCK SETTINGS	Medium compression, medium rebound, air volume spacer 0.2
FORK	Fox 38 29 Float FIT GRIP EVOL Performance, 160mm, e-bike tuned, tapered steerer tube, Boost 15x110mm axle, 44mm offset. Settings: 3 positions with micro adjust compression, low-speed rebound, air preload
HEADSET	Acros AZF-601 R1 Block Lock 120°, ZS44/28.6 top, ZS56/40 bottom
STEM	Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm barbare
HANDLEBAR	Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbare
GRIPS	Onoff Desert, 1lock-on, 135mm
SEATPOST	Onoff Pija dropper internal, diameter 31.6mm, 1X Remote lever with bearing, S size: 405x95-125mm, M size: 458x120-150mm, L size: 498x140-170mm, XL size: 558x170-200mm
SADDLE	FIZIK Terra Aidon X5 145mm
FRONT BRAKE	Sram DB8, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads
REAR BRAKE	Sram DB8, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads
BRAKE LEVER	Sram DB8, tool reach adjust, lever pivot bushings
RIMS	Mavic E-Deemax 29, 30mm internal width, welded, PFP, tubeless ready, 28 spokes
SPOKES	Mavic J-bend double butted, contactless lacing
FRONT HUB	Mavic, Boost 15x110mm, IS 6 bolts
REAR HUB	Mavic, Boost 12x148mm, ID360 Ratchet system, IS 6 bolts, HG freehub

FRONT TIRE	Maxxis Minion DHF 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead
REAR TIRE	Maxxis Minion DHR II 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead
CRANKSET	Shimano Steps FC-EM600 ebike, 165mm
RINGS	Sram X-Sync 2 Eagle 34T, alloy, narrow-wide, 104 BCD
BOTTOM BRACKET	--
PEDALS	--
CHAIN	Sram SX Eagle, 12s, Powerlock
FRONT DERRAILLEUR	--
REAR DERRAILLEUR	Sram GX Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1
SHIFT LEVERS	Sram Trigger NX Eagle, 12s, X-Actuation 1:1, single click
CASSETTE	Sram PG-1210, 11-50T, 12s
MOTOR	Shimano STEPS EP801
BATTERY	Simplo internal 720Wh G3
DISPLAY	Shimano EN600
DERAILLEUR HANGER	Mondraker M068
OTHERS	--
WEIGHT	--