

DUNE CARBON XR

Black / Mars / Racing Silver

FRAME	Stealth Air full Carbon, e-Bike Optimized Zero Suspension System, Mullet, 165mm travel, Forward Geometry, internal & removable battery, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 15mm axles, exclusive plastic motor covers	REAR HUB	e*thirteen Boost 12x148mm, triple-sealed, fully machined aluminum w/6-degree engagement, IS 6 bolts, XD freehub
SIZES	S: 380mm / M: 420mm / L: 450mm / XL: 490mm	FRONT TIRE	Maxxis Assegai 29x2.5WT, tubeless ready, 3C MaxxGrip compound, EXO+ casing, 60TPI, folding bead
REAR SHOCK	Öhlins TTX22M.2 205x65mm. Settings: high speed compression lever with climb mode, low-speed compression, rebound, spring preload, Trunnion top mount, 30x8mm bottom bushings	REAR TIRE	Maxxis Minion DHR II 27,5x2.4 WT, tubeless ready, 3C MaxxTerra compound, DD casing, 2x120TPI, folding bead
SHOCK SETTINGS	C10 compression, R35 rebound, Spring rate: S size 343 lbs, M size 411 lbs, L size 457 lbs, XL size 502 lbs	CRANKSET	E.13 TRS Race carbon ebike, S size: 165mm M size: 165mm L size: 170mm XL size: 170mm
FORK	Öhlins RXF 38 M.2 29, 180mm, TTX18 Twin Tube cartridge, tapered steerer tube, Boost 15x110mm axle, offset 44mm. Settings: high speed compression lever with climb mode, low-speed compression, rebound, air preload, ramp chamber	RINGS	Sram X-Sync 2 Eagle 34T T-Type, steel, narrow-wide, 104 BCD CL55
HEADSET	Acros custom for 1-1/2" head tube, angular contact bearings 40x52x7, Internal cable routing	CHAIN	Sram X0 Eagle T-Type, 12s, Powerlock
STEM	Onoff Krypton FG 30mm, CNC, 31,8mm barbare	REAR DERRAILLEUR	Sram X0 Eagle AXS, T-Type roller bearing clutch, cage lock, long carbon cage, 1x12s
HANDLEBAR	Onoff Krypton Carbon 1.0, rise: 25mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbare	SHIFT LEVERS	Sram Eagle AXS Pod MMX, 12s
GRIPS	Onoff Desert, 1lock-on, 135mm	CASSETTE	Sram XS-1295, 10-52T, T-Type, 12s
SEATPOST	RockShox Reverb Stealth AXS, diameter 31.6mm S size: 340x125mm M size: 390x150mm L size: 440x170mm XL size: 440x170mm	MOTOR	Bosch Performance Line SX (25Km/h) GEN4 SMART SYSTEM Diagonal, Wide
SADDLE	Fizik Terra Aidon Slim X5, 145mm	BATTERY	Bosch Compact Powertube 400Wh
FRONT BRAKE	Sram Code Ultimate Stealth, oversized 4-piston caliper, HS2 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads	DISPLAY	Bosch Kiox 500 / Bosch Mini Remote / Bosch System Controller
REAR BRAKE	Sram Code Ultimate Stealth, oversized 4-piston caliper, HS2 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads	DERAILLEUR HANGER	--
BRAKE LEVER	Sram Code Ultimate Stealth, SwingLink and lever pivot bearings, tools-free reach and contact point adjust	OTHERS	--
RIMS	e*thirteen Grappler Race Carbon, Hookless carbon rim, 30mm internal width, tubeless ready, 28 spokes, 29 front, 27,5 rear	WEIGHT	--
SPOKES	e*thirteen custom Hive triple-buttet black steel, alloy nipples, nipple washers		
FRONT HUB	e*thirteen Boost 15x110mm, triple-sealed, fully machined aluminum, IS 6 bolts		

DUNE CARBON RR

Bronze / Vortex Grey / Frog Grey

FRAME	Stealth Air full Carbon, e-Bike Optimized Zero Suspension System, Mullet, 165mm travel, Forward Geometry, internal & removable battery, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 15mm axles, exclusive plastic motor covers	FRONT TIRE	Maxxis Assegai 29x2.5WT, tubeless ready, 3C MaxxGrip compound, EXO+ casing, 60TPI, folding bead
SIZES	S: 380mm / M: 420mm / L: 450mm / XL: 490mm	REAR TIRE	Maxxis Minion DHR II 27.5x2.4 WT, tubeless ready, 3C MaxxTerra compound, DD casing, 2x120TPI, folding bead
REAR SHOCK	Öhlins TTX Air 205X65mm. Settings: high speed compression lever with climb mode, low-speed compression, rebound, air preload, Trunion top mount, 30x8mm bottom bushings	CRANKSET	E.13 E*Spec Plus, S size: 165mm M size: 165mm L size: 170mm XL size: 170mm
SHOCK SETTINGS	C20 compression, R35 rebound, Volume reducers 12.000 (2xF+1D)	RINGS	Sram X-Sync 2 Eagle 34T T-Type, steel, narrow-wide, 104 BCD CL55
FORK	Öhlins RXF 38 M.2 29, 170mm, TTX18 Twin Tube cartridge, tapered steerer tube, Boost 15x110mm axle, offset 44mm. Settings: high speed compression lever with climb mode, low-speed compression, rebound, air preload, ramp chamber	CHAIN	Sram GX Eagle T-Type, 12s, Powerlock
HEADSET	Acros custom for 1-1/2" head tube, angular contact bearings 40x52x7, Internal cable routing	REAR DERRAILLEUR	Sram GX Eagle AXS, T-Type roller bearing clutch, cage lock, 1x12s
STEM	Onoff Krypton FG 30mm, CNC, 31.8mm barbare	SHIFT LEVERS	Sram Eagle AXS Pod MMX, 12s
HANDLEBAR	Onoff Krypton Carbon 1.0, rise: 25mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbare	CASSETTE	Sram XS-1275, 10-52T, T-Type, 12s
GRIPS	Onoff Desert, 1lock-on, 135mm	MOTOR	Bosch Performance Line SX (25Km/h) GEN4 SMART SYSTEM Diagonal, Wide
SEATPOST	Onoff Pija dropper internal, diameter 31.6mm, IX Remote lever with bearing, S size: 405x95-125mm, M size: 458x120-150mm, L size: 498x140-170mm, XL size: 558x170-200mm	BATTERY	Bosch Compact Powertube 400Wh
SADDLE	Fizik Terra Aidon Slim X5, 145mm	DISPLAY	Bosch Kiox 500 / Bosch Mini Remote / Bosch System Controller
FRONT BRAKE	Sram Code Bronze Stealth, oversized 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads	DERAILLEUR HANGER	--
REAR BRAKE	Sram Code Bronze Stealth, oversized 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads	OTHERS	--
BRAKE LEVER	Sram Code Bronze Stealth, SwingLink and lever pivot bushings, tool-free reach adjust	WEIGHT	--
RIMS	e*thirteen Grappler Race, Hookless 6069 Welded Aluminum 30mm internal width, tubeless ready, 28F / 32R spokes 29 front, 27.5 rear		
SPOKES	e*thirteen custom J-bend, triple-buttet steel, alloy nipples, nipple washers		
FRONT HUB	e*thirteen Boost 15x110mm, triple-sealed, fully machined aluminum, IS 6 bolts		
REAR HUB	e*thirteen Boost 12x148mm, triple-sealed, fully machined aluminum w/6-degree engagement, IS 6 bolts, XD freehub		



DUNE CARBON R

Racing Silver / Black / Flame Red

FRAME	Stealth Air full Carbon, e-Bike Optimized Zero Suspension System, Mullet, 165mm travel, Forward Geometry, internal & removable battery, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 15mm axles, exclusive plastic motor covers	FRONT TIRE	Maxxis Assegai 29x2.5WT, tubeless ready, 3C MaxxGrip compound, EXO+ casing, 60TPI, folding bead
SIZES	S: 380mm / M: 420mm / L: 450mm / XL: 490mm	REAR TIRE	Maxxis Minion DHR II 27.5x2.4 WT, tubeless ready, 3C MaxxTerra compound, DD casing, 2x120TPI, folding bead
REAR SHOCK	Fox Float X Performance EVOL, 205x65mm. Settings: 2-position compression (Open/Firm), rebound, air preload, Trunnion top mount, 30x8mm bottom bushings	CRANKSET	E.13 E*Spec Plus, S size: 165mm M size: 165mm L size: 170mm XL size: 170mm
SHOCK SETTINGS	Medium compression, medium rebound, air volume spacer 0.4	RINGS	Sram X-Sync 2 Eagle 34T, steel, narrow-wide, 104 BCD
FORK	FOX 38 Float 3P Performance Grip, 170mm, e-bike tuned, tapered steerer tube, Boost 15x110mm axle, 44mm offset. Settings: 3 positions with micro adjust compression, low-speed rebound, air preload	CHAIN	Sram NX Eagle, 12s, Powerlock
HEADSET	Acros custom for 1-1/2" head tube, angular contact bearings 40x52x7, Internal cable routing	REAR DERRAILLEUR	Sram GX Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1
STEM	Onoff Krypton FG 30mm, CNC, 31.8mm barbare	SHIFT LEVERS	Sram Trigger NX Eagle, 12s, X-Actuation 1:1, single click
HANDLEBAR	Onoff Krypton 1.0, rise: 25mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbare	CASSETTE	Sram PG-1230, 11-50T, 12s
GRIPS	Onoff Desert, 1lock-on, 135mm	MOTOR	Bosch Performance Line SX (25Km/h) GEN4 SMART SYSTEM Diagonal, Wide
SEATPOST	Onoff Pija dropper internal, diameter 31.6mm, 1X Remote lever with bearing, S size: 405x95-125mm, M size: 458x120-150mm, L size: 498x140-170mm, XL size: 558x170-200mm	BATTERY	Bosch Compact Powertube 400Wh
SADDLE	Fizik Terra Aidon Slim X5, 145mm	DISPLAY	Bosch Kiox 500 / Bosch Mini Remote / Bosch System Controller
FRONT BRAKE	Sram DB8, oversized 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads	DERAILLEUR HANGER	Sram UDH
REAR BRAKE	Sram DB8, oversized 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads	OTHERS	--
BRAKE LEVER	Sram DB8, tool reach adjust, lever pivot bushings	WEIGHT	--
RIMS	e*thirteen Grappler Core, Hookless 6069 Welded Aluminum 30mm internal width, tubeless ready, 28F / 28R spokes 29 front, 27.5 rear		
SPOKES	e*thirteen custom J-bend, triple-buttet steel, alloy nipples, nipple washers		
FRONT HUB	e*thirteen Boost 15x110mm, triple-sealed, fully machined aluminum, IS 6 bolts		
REAR HUB	e*thirteen Boost 12x148mm, triple-sealed, fully machined aluminum w/6-degree engagement, IS 6 bolts		

